



विक्टोरिया मेमोरियल हाल

VICTORIA MEMORIAL HALL

(भारत सरकार के संस्कृति मंत्रालय के प्रशासनिक नियंत्रण के तहत एक स्वायत्त संगठन)

(An autonomous organisation under the administrative control of the Ministry of Culture, Govt. of India)

1, क्वीन्स वे, कोलकाता - 700 071

1, Queen's Way, Kolkata - 700 071

V. M. No 548 /2021

15 April 2021

NOTICE INVITING QUOTATIONS

Sealed Tenders are invited from authorized dealers of 6 KVA Online UPS (Excluding UPS Batteries) of reputed manufactures with the specification given in the **Annexure**.

The tenderers are to submit their tenders in the letter heads addressed to Secretary & Curator, Victoria Memorial Hall, 1, Queen's Way, Kolkata – 700 071 by 12 noon of 28.04.2021, which will be opened at 2 PM on the same date in presence of tenderers or their representatives if any.

The tenderers, alongwith their tenders, are to submit photocopies of PAN Card, GST Certificates, Dealership Certificate.

The tenderers are to submit rate for one 6 KVA Online UPS as per specification given separately inclusive of taxes and charges, if any. The supply of UPS is to be made at the aforesaid address of Victoria Memorial Hall (VMH) within seven days of the issue of the order by VMH.

Payment will be made after satisfactory supply of the UPS on production of bills and challans in triplicate.

VMH reserves the right to accept or cancel any tender without giving any reason.


Secretary & Curator

Copy to

1. The Accounts Officer, VMH
2. The Security Officer, VMH
3. The Office Superintendent, VMH
4. Storekeeper, VMH
5. Shri Dipankar Samanta to upload the NIQ in the VMH website

☎ : 2223-1890/1891/0953/5142 • फैक्स/Fax : +91-33-2223-5142

ई-मेल/E-mail : victomem@gmail.com • वेबसाइट/Website : www.victoriame-morial-cal.org

Annexure

Specification for 6 KVA Online UPS (Excluding UPS Battery).

Rating	: 6 KVA
Power factor	: 0.98 to Unity
Input Termination	: Single Phase, 02 Wire Plus Earth
Input Voltage	: 160 to 300 VAC, 40 to 60 Hz
Output Voltage	: 230 VAC +/- 1%, 50 Hz, Pure Sine wave.
Battery Bank Voltage	: 192 V
Charger Type	: Solid State Float cum boost with automatic boost / trickle charge mode with current limit feature.
Transfer time	: 0 MS
Bypass	: Internal Static by pass
Audible Alarm	: Generation of Audible Alarm for AC Failure, Battery Low and UPS fault
Protection	: Electronic Protection for Output Overload, Short Circuit, Over Temp, Battery Low, Over Charge
Operating Temperature	: 0 to 40° C
Humidity	: 0 to 90% Non- Condensing
Warranty	: 03 (three) Years.